

Lift&Drive

70E/ES and 90E/ES



Lift&Drive 70E/ES and 90E/ES

The Lift&Drive 70 and 90E/ES are our neat and maneuverable lifting trolleys, designed with a special focus on ergonomics. The chassis of the trolleys is merely 435 mm wide, making them very light and flexible. We offer a standard version of the trolley, but we have also developed ones that are specifically developed to be used in environments such as larger catering establishments, archives, and pharmacies, where they go by the name "crate lifter".

There are a large number of standard tools to choose from. The masts are equipped with screw drives and are available in different heights. Despite their slight weight the trolleys can handle weights up to either 70 or 90 kg. To ensure maximal safety the trolleys possess a built-in release function, which serves as protection from crushing injuries and prevents the trolley from tipping over.

Technical Specifikations for the 70E/ES and 90E/ES

139, 110 mm

735, 716 mm

440x498 mm

80/100, 50/75 mm

498 mm

Mast	Overall height, standard	Overall height, low-built	Total lifting height, standard	Total lifting height, low-built	Length of stroke
-250	1442	1413	1123	1094	984
standard	1692	1663	1373	1344	1234
+250	1942	1913	1623	1594	1484
+500	2192	2163	1873	1844	1734

Minimum lifting height, standard, low-built

Total width

Length (without loading platform) standard, low-built

Loading platform (L x W)

Wheel diameter (front/rear) standard, low-built

Max load 70E, 70ES70 kgMax load 90E, 90ES90 kgDead weight33 kgBattery voltage24 VBattery capacity6.5 Ah

Charging voltage 230VAC/50Hz or 115VAC/60Hz

Material, Lift&Drive 70E, 90E Chassis in powder-coated steel

Material, Lift&Drive 70ES, 90ES Chassis in stainless steel

Platform can if necessary be moved up 110 mm in the sledge.

For further info please contact your sales representative

PRONOMIC AB info@pronomic.se www.pronomic.se

SMEYERS-TU

 B-1853 Strombeek-Bever

One of our main strengths is that we're in charge of both design and production.

